

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : SWIMMING POOL PAINT -WHITE
 Product code : E1100

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Crown Paint Company
 1801 W. Sheridan
 Oklahoma City, 73106 - United States
 T 1-405-232-8580

1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:
 in Canada call CANUTEC at 613-996-6666 or *666 on a cellular phone.
 in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification


Flam. Liq. 3 H226 - Flammable liquid and vapor
 Muta. 1B H340 - May cause genetic defects
 Carc. 1B H350 - May cause cancer

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
 H340 - May cause genetic defects
 H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical/ventilating/lighting equipment
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2) to extinguish
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	20 - 30	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
titanium(IV) oxide	(CAS-No.) 13463-67-7	10 - 20	Carc. 2, H351
distillates, hydrotreated light	(CAS-No.) 64742-47-8	< 5	Asp. Tox. 1, H304
naphtha, heavy aromatic	(CAS-No.) 64742-94-5	< 5	Asp. Tox. 1, H304

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

solvent naphtha (petroleum), light aromatic (64742-95-6)		
ACGIH	ACGIH TWA (ppm)	50 ppm

titanium(IV) oxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (Titanium dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Hand protection : Protective gloves.
- Eye protection : Safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear respiratory protection.
- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
: No data available
: No data available
- Odor threshold : No data available
- pH : No data available
- Melting point : Not applicable
- Freezing point : No data available
- Boiling point : 148.9 - 158.9 °C
300 - 318 °F
- Flash point : 42.2 °C
108 °F
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : 0.7 - 12.6 vol %

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.429 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

VOC content (Regulatory - Less water and exempt solvents)	: 473.21 g/l
	: 3.949 lb/gal
VOC content (Material - Actual)	: 473.21 g/l
	: 3.949 lb/gal
Percent Solids (Weight)	: 66.81 %
Percent Solids (Volume)	: 44.542 %
Percent Volatile (Weight)	: 33.19 %
Percent Volatile (Volume)	: 55.458 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

naphtha,heavy aromatic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
LC50 inhalation rat (mg/l)	> 5 mg/l (4 h, Rat, Inhalation)
titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

titanium(IV) oxide (13463-67-7)	
IARC group	2B - Possibly Carcinogenic to Humans

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

Specific target organ toxicity – repeated exposure	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

naphtha,heavy aromatic (64742-94-5)	
LC50 fish 1	2.34 mg/l (96 h, Oncorhynchus mykiss, Fresh water)
EC50 Daphnia 1	0.95 mg/l (48 h, Daphnia magna)

titanium(IV) oxide (13463-67-7)	
EC50 Daphnia 1	> 100 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Weight of evidence)
Threshold limit algae 1	61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

naphtha,heavy aromatic (64742-94-5)	
Persistence and degradability	Not readily biodegradable in water.

titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable. Low potential for mobility in soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

naphtha,heavy aromatic (64742-94-5)	
Log Pow	2.9 - 6.1
Bioaccumulative potential	Bioaccumable.

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6

titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1263 Paint, 3, III
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

Transportation of Dangerous Goods

- Transport document description : UN1263 PAINT, 3, III
UN-No. (TDG) : UN1263
Proper Shipping Name (Transportation of Dangerous Goods) : PAINT
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Packing group : III - Minor Danger

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass), 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

Transport by sea

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

SWIMMING POOL PAINT -WHITE

Listed on the Canadian DSL (Domestic Substances List) inventory.

naphtha, heavy aromatic (64742-94-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

titanium(IV) oxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 06/11/2019

SWIMMING POOL PAINT -WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer

SDS US Endura

The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.