

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : WATER REDUCIBLE ENAMEL - TIGER BROWN  
 Product code : E186

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Crown Paint Company  
 1801 W. Sheridan  
 Oklahoma City, 73106 - United States  
 T 1-405-232-8580

#### 1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:  
 in Canada call CANUTEC at 613-996-6666 or \*666 on a cellular phone.  
 in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 3 H226 - Flammable liquid and vapor  
 Skin Irrit. 2 H315 - Causes skin irritation  
 Eye Irrit. 2 H319 - Causes serious eye irritation  
 Muta. 1B H340 - May cause genetic defects  
 Carc. 1B H350 - May cause cancer

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
 H315 - Causes skin irritation  
 H319 - Causes serious eye irritation  
 H340 - May cause genetic defects  
 H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P233 - Keep container tightly closed.  
 P240 - Ground/Bond container and receiving equipment  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P264 - Wash thoroughly after handling  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P308+P313 - If exposed or concerned: Get medical advice/attention.  
 P321 - Specific treatment (see 4.1. First aid procedures on this label)

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Butyl Cellosolve (EB)	(CAS-No.) 111-76-2	10 - 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2-butanol	(CAS-No.) 78-92-2	5 - 10	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 3, H336
ammonia, conc=2%, aqueous solution	(CAS-No.) 1336-21-6	< 5	Skin Corr. 1B, H314 Aquatic Acute 1, H400
carbon black	(CAS-No.) 1333-86-4	< 5	Carc. 2, H351
cobalt(II) 2-ethylhexanoate	(CAS-No.) 136-52-7	0.146 - 0.219	Carc. 2, H351
naphtha (petroleum), hydrotreated heavy	(CAS-No.) 64742-48-9	0.102 - 0.219	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately. If skin irritation occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation.  
Symptoms/effects after eye contact : Irritation to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.  
Reactivity : Flammable liquid and vapor.

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

2-butanol (78-92-2)		
ACGIH	ACGIH TWA (ppm)	100 ppm (sec-Butanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	URT irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	150 ppm

Butyl Cellosolve (EB) (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (Carbon black; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear respiratory protection.
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: No data available
	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 36.1 - 171.1 °C 97 - 340 °F
Flash point	: 53.3 °C 128 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: 1.1 - 10.6 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.03 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

VOC content (Regulatory - Less water and exempt solvents)	: 385.2 g/l 3.215 lb/gal
VOC content (Material - Actual)	: 168.7 g/l 1.408 lb/gal
Percent Solids (Weight)	: 29.28 %
Percent Solids (Volume)	: 24.384 %
Percent Volatile (Weight)	: 70.72 %

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Percent Volatile (Volume) : 75.616 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>2-butanol (78-92-2)</b>	
LD50 oral rat	2193 mg/kg (Rat)
LD50 dermal rat	> 2000 mg/kg (Rat)
LC50 inhalation rat (mg/l)	48.5 mg/l/4h (Rat)
ATE US (oral)	2193 mg/kg body weight
ATE US (vapors)	48.5 mg/l/4h
ATE US (dust, mist)	48.5 mg/l/4h

<b>Butyl Cellosolve (EB) (111-76-2)</b>	
LD50 oral rat	1746 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
ATE US (oral)	1746 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	450 ppmV/4h
ATE US (vapors)	2.2 mg/l/4h
ATE US (dust, mist)	2.2 mg/l/4h

<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
LD50 oral rat	3129 mg/kg body weight (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Weight of evidence; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	3129 mg/kg body weight

<b>carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.

<b>Butyl Cellosolve (EB) (111-76-2)</b>	
IARC group	3 - Not Classifiable

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
IARC group	2B - Possibly Carcinogenic to Humans

<b>carbon black (1333-86-4)</b>	
IARC group	2B - Possibly Carcinogenic to Humans

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Irritation to eyes.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

<b>2-butanol (78-92-2)</b>	
LC50 fish 1	3670 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 2	2300 mg/l (EC50; 24 h)

<b>Butyl Cellosolve (EB) (111-76-2)</b>	
LC50 fish 1	1474 ppm (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Static system; Fresh water; Experimental value)
EC50 Daphnia 1	1550 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	911 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Threshold limit algae 2	88 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
LC50 fish 1	46.51 mg/l (LOEC; ASTM; 96 h; Pimephales promelas; Flow-through system; Fresh water; Read-across)
EC50 Daphnia 1	0.212 mg/l (NOEC; ASTM; 48 h; Ceriodaphnia dubia; Static system; Salt water; Read-across)
LC50 fish 2	54.1 mg/l (LC50; ASTM; 96 h; Pimephales promelas; Flow-through system; Fresh water; Read-across)
EC50 Daphnia 2	0.605 mg/l (LC50; ASTM; 48 h; Ceriodaphnia dubia; Static system; Salt water; Read-across)
Threshold limit algae 1	144 µg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Read-across)
Threshold limit algae 2	32.2 µg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Read-across)

<b>carbon black (1333-86-4)</b>	
LC50 fish 1	> 1000 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio)
EC50 Daphnia 1	> 5600 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water)
LC50 fish 2	1000 mg/l (LC0; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	> 10000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>2-butanol (78-92-2)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	1.87 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.47 g O <sub>2</sub> /g substance

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-butanol (78-92-2)</b>	
ThOD	2.59 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.72
<b>Butyl Cellosolve (EB) (111-76-2)</b>	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.
<b>ammonia, conc=2%, aqueous solution (1336-21-6)</b>	
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Biodegradable in the soil. No (test) data on mobility of the components available. Ozonation in the air.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
Persistence and degradability	Readily biodegradable in water. No (test) data on mobility of the substance available.
<b>carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil.
ThOD	Not applicable

### 12.3. Bioaccumulative potential

<b>2-butanol (78-92-2)</b>	
Log Pow	0.61 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Butyl Cellosolve (EB) (111-76-2)</b>	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>ammonia, conc=2%, aqueous solution (1336-21-6)</b>	
Log Pow	-1.14
Bioaccumulative potential	Bioaccumulation: not applicable.
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
BCF fish 1	1.2 (BCF; 131 days; Seriola quinqueradiata; Static system; Salt water; Read-across)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

<b>2-butanol (78-92-2)</b>	
Surface tension	0.023 N/m (20 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
<b>Butyl Cellosolve (EB) (111-76-2)</b>	
Surface tension	0.065 N/m (20 °C; Calculated value)
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
Surface tension	0.064 N/m (20 °C; 1 g/l)
<b>carbon black (1333-86-4)</b>	
Ecology - soil	Not toxic to plants. Not toxic to animals.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapors may accumulate in the container.

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

#### Transportation of Dangerous Goods

Transport document description : UN1263 PAINT, 3, III

UN-No. (TDG) : UN1263

Proper Shipping Name (Transportation of Dangerous Goods) : PAINT

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group : III - Minor Danger



# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass), 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

### Transport by sea

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-butanol	CAS-No. 78-92-2	5 - 10%
ammonia, conc=2%, aqueous solution	CAS-No. 1336-21-6	< 5%
<b>2-butanol (78-92-2)</b>		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting	1 %	
<b>ammonia, conc=2%, aqueous solution (1336-21-6)</b>		
Listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	1000 lb	

### 15.2. International regulations

#### CANADA

##### WATER REDUCIBLE ENAMEL - TIGER BROWN

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### 2-butanol (78-92-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### naphtha (petroleum), hydrotreated heavy (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

### EU-Regulations

No additional information available

### National regulations

##### carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

# WATER REDUCIBLE ENAMEL - TIGER BROWN

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

carbon black (1333-86-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

2-butanol (78-92-2)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Butyl Cellosolve (EB) (111-76-2)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

ammonia, conc=2%, aqueous solution (1336-21-6)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

carbon black (1333-86-4)
U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

Revision date : 06/10/2019

Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life

SDS US Endura

*The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.*