

Liquid Paint Remover

Technical Data Sheet (TDS)

Product Description

Crown Liquid Paint Remover is a professional grade fast acting paint stripper. Crown Liquid Paint Remover efficiently removes many coating types from many surfaces.

Product features:

- Efficient removal of old finishes
- Clings to incline and vertical surfaces
- No Flashpoint
- Phenol free

Recommended Uses

Crown Liquid Paint Remover is intended for industrial applications; either new build or maintenance applications.

Crown Liquid Paint Remover removes multiple coats the following types of coatings from wood, metal and masonry surfaces:

- Baked enamels
- Acrylic lacquers
- Varnishes
- Alkyd Enamels
- Epoxies
- Polyurethanes

Mixing

Crown Liquid Paint Remover is a single component ready to use product.

Shake each container thoroughly prior to use.

Open container slowly to relieve the pressure.

Product Characteristics

Volume Solids: 7% +/- 1%

pH: 3

Shelf Life: 3 years at 77°F (25°C)

Note: For unopened product.

IMPORTANT NOTE: KEEP FROM FREEZING

101618 Version Date: June 5,2019

Version No: 1.4

Surface Prep

Remove any hardware from the article that does not require coating removal prior to the application of **Crown Liquid Paint Remover**. Use masking tape to cover any hardware that cannot be removed, mask off all plastic and rubber surfaces. Protect surrounding areas with a heavy, plastic drop cloth.

Application Method

IMPORTANT SAFETY NOTE:

- Personnel should wear **GLOVES, BOOTS, GOGGLES or FACE SHIELD and PROTECTIVE CLOTHING.**
- Avoid prolonged contact with skin. **KEEP AWAY** from eyes. Should eye contact occur, flush with water for 15 minutes; Consult a physician.
- Use of a fresh air respirator is recommended.

DO NOT USE IN CONFINED SPACES

1. Surface should be dry and below 110F (43 C)
2. Pour into a metal or plastic container and apply a thick coat with a paint brush.
3. Leave the applied area and let the stripper do its work.
4. Allow a minimum of 5 minutes for product to work. Time can vary up to 45 minutes for most finishes. Avoid thin coats of stripper as this will dry too quickly and not let the remover to work effectively.
5. After 15 minutes, test a small area by scraping to see if finish is ready for removal.
6. Multiple coats for stubborn finishes may require repeat application.

Liquid Paint Remover

Technical Data Sheet (TDS)

Note: On particularly tough finishes and to minimize evaporation, cover area with a 2-3 mil polyethylene film over wet removers. For best results, let the remover stand up to two hours, and if necessary, repeat with a second application.

If the stripper dries on the surface, scrape loosened portions and reapply as needed.

Note: Do not use on linoleum, plastic, rubber, asphalt tile, fiberglass or other synthetics.

Ordering Information (sizing)

Available in 5-gallon pails and 55-gallon drums.

Disposal

Store all paint residue and solid waste in a metal container.

Dispose of in accordance with local requirements. Contact your local sanitation department or waste disposal contractor for more information.

Storage Conditions

Assure that the lid is well secured.

Store at temperatures of at 77°F (25°C) or below, higher temperatures will increase the internal pressure within the can and may push the lid off.

Keep away from heat or open flame.

IMPORTANT NOTE: KEEP FROM FREEZING

Safety Precautions

Please refer to all Safety Data Sheets (SDS) before using this product. SDS sheets can be obtained by contacting Crown Paint.