

### SECTION 1: Identification

#### 1.1. Identification

Product form : Substance  
 Trade name : AROMATIC 100  
 CAS-No. : 64742-95-6  
 Product code : TS116  
 BIG no : F06737

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Crown Paint Company  
 1801 W. Sheridan  
 Oklahoma City, 73106 - United States  
 T 1-405-232-8580

#### 1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:  
 in Canada call CANUTEC at 613-996-6666 or \*666 on a cellular phone.  
 in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 3	H226 - Flammable liquid and vapor
Acute Tox. 4 (Inhalation:dust,mist)	H332 - Harmful if inhaled
Skin Irrit. 2	H315 - Causes skin irritation
Muta. 1B	H340 - May cause genetic defects
Carc. 1B	H350 - May cause cancer
STOT SE 3	H335 - May cause respiratory irritation
STOT RE 2	H373 - May cause damage to organs through prolonged or repeated exposure
Asp. Tox. 1	H304 - May be fatal if swallowed and enters airways

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
 H304 - May be fatal if swallowed and enters airways  
 H315 - Causes skin irritation  
 H332 - Harmful if inhaled  
 H335 - May cause respiratory irritation  
 H340 - May cause genetic defects  
 H350 - May cause cancer  
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P233 - Keep container tightly closed.  
 P240 - Ground/Bond container and receiving equipment  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center/doctor/physician if you feel unwell  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see 4.1. First aid procedures on this label)  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Name : solvent naphtha (petroleum), light aromatic  
CAS-No. : 64742-95-6

Name	Product identifier	%	GHS-US classification
solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	60 - 70	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
1,2,4-trimethylbenzene	(CAS-No.) 95-63-6	30 - 40	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 STOT SE 3, H335 Aquatic Chronic 2, H411
xylene, mixture of isomers	(CAS-No.) 1330-20-7	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
cumene	(CAS-No.) 98-82-8	< 5	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylbenzene	(CAS-No.) 100-41-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Remove/Take off all contaminated clothing immediately. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see 4.1. First aid procedures on this label).
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: No unsuitable extinguishing media known. Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	--

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

#### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. On land, sweep or shovel into suitable containers. Collect spillage. Minimize generation of dust. Store away from other materials.
-------------------------	--

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
-----------------------------------	--

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.
- Hygiene measures : Wash thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep container tightly closed.
- Incompatible products : Strong bases. strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

AROMATIC 100 (64742-95-6)		
ACGIH	ACGIH TWA (ppm)	50 ppm
solvent naphtha (petroleum), light aromatic (64742-95-6)		
ACGIH	ACGIH TWA (ppm)	50 ppm
1,2,4-trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
xylene, mixture of isomers (1330-20-7)		
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	50 ppm (Cumene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye, skin, & URT irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: Wear approved mask. In case of insufficient ventilation, wear suitable respiratory equipment. Wear respiratory protection.
Other information	: When using, do not eat, drink or smoke.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: No data available
	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 135 - 210 °C
Flash point	: 46 °C 114.8 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: < 1100 hPa (50 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: Water: < 0.01 g/100ml
Log Pow	: 2.1 - 6
Auto-ignition temperature	: 485 °C 905 °F
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: 0.75 cSt
Viscosity, dynamic	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Not established. Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>AROMATIC 100 (64742-95-6)</b>	
ATE US (dust, mist)	3.261 mg/l/4h

<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
ATE US (vapors)	18 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>xylene, mixture of isomers (1330-20-7)</b>	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	29 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>cumene (98-82-8)</b>	
LD50 oral rat	> 2000 mg/kg (Rat; Other; Literature study; 4000 mg/kg bodyweight; Rat; Other; Inconclusive, insufficient data)
LD50 dermal rabbit	10578 mg/kg (Rabbit; Literature study; Other)
LC50 inhalation rat (mg/l)	40 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	8000 ppm/4h (Rat; Literature study)
ATE US (dermal)	10578 mg/kg body weight
ATE US (gases)	8000 ppmV/4h
ATE US (vapors)	40 mg/l/4h
ATE US (dust, mist)	40 mg/l/4h

<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15415 mg/kg body weight
ATE US (gases)	4000 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

<b>xylene, mixture of isomers (1330-20-7)</b>	
IARC group	3 - Not Classifiable

<b>cumene (98-82-8)</b>	
IARC group	2B - Possibly Carcinogenic to Humans

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly Carcinogenic to Humans

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if inhaled.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Dangerous for the environment.
Ecology - air	: TA-Luft Klasse 5.2.7.1.1/II.
Ecology - water	: Severe water pollutant (surface water). Contains ground water contaminating component(s). Toxic to aquatic organisms.

1,2,4-trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	2.356 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)

  

cumene (98-82-8)	
EC50 Daphnia 1	2.14 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

  

ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)

#### 12.2. Persistence and degradability

AROMATIC 100 (64742-95-6)	
Persistence and degradability	Not established.

  

1,2,4-trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O <sub>2</sub> /g substance

  

xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.

  

cumene (98-82-8)	
Persistence and degradability	Inherently biodegradable. Not readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.28 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.42 g O <sub>2</sub> /g substance
ThOD	3.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.4

  

ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance
BOD (% of ThOD)	45.4 (20 days)

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.3. Bioaccumulative potential

<b>AROMATIC 100 (64742-95-6)</b>	
Log Pow	2.1 - 6
Bioaccumulative potential	Not established.
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Log Pow	2.1 - 6
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation ( $4 \geq \text{Log Kow} \leq 5$ ).
<b>xylene, mixture of isomers (1330-20-7)</b>	
BCF fish 2	7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Log Pow	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>cumene (98-82-8)</b>	
BCF fish 1	35.5 (BCF)
BCF other aquatic organisms 1	94.69 (BCF; BCFBAF v3.00)
Log Pow	3.66 (Experimental value; 3.55; Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>ethylbenzene (100-41-4)</b>	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

<b>1,2,4-trimethylbenzene (95-63-6)</b>	
Surface tension	0.029 N/m
Log Koc	log Koc,3.04; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
<b>xylene, mixture of isomers (1330-20-7)</b>	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
<b>cumene (98-82-8)</b>	
Log Koc	Koc,884; Calculated value; log Koc; 2.946; Calculated value
<b>ethylbenzene (100-41-4)</b>	
Surface tension	0.029 N/m
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value

### 12.5. Other adverse effects

Other information : Avoid release to the environment.



# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Incinerate under surveillance with energy recovery. Do not discharge into drains or the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with all local, regional, national and international regulations.
- Additional information : Hazardous waste according to Directive 2008/98/EC. Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1268 Petroleum products, n.o.s (Combustible Liquid), 3, III
- UN-No.(DOT) : UN1268
- Proper Shipping Name (DOT) : Petroleum products, n.o.s  
Combustible Liquid
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.  
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

### Transportation of Dangerous Goods

Transport document description : UN1268 PETROLEUM PRODUCTS, N.O.S. (Combustible Liquid), 3, III

UN-No. (TDG) : UN1268

Proper Shipping Name (Transportation of Dangerous Goods) : PETROLEUM PRODUCTS, N.O.S.

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group : III - Minor Danger

TDG Special Provisions : 91 - Despite paragraph 13.1.5(c) of CGSB-43.146, these dangerous goods may, after January 1, 2010, be handled, offered for transport or transported in a means of containment on a road vehicle, a railway vehicle or a ship on a domestic voyage if the means of containment was manufactured before January 1, 2003 and the following information is set out on a metal label in a holder that is welded to the tank head or to another readily visible location on the tank: (a) the name of the tank's manufacturer; (b) the metal thickness of the tank in millimetres; (c) the capacity of the tank in litres; (d) the year that the tank was manufactured; (e) the label of the Underwriters' Laboratories of Canada (ULC); (f) the words "Mobile Refuelling Tank – ULC/ORD-C142.13"; (g) the words "Not Authorized for Transport of Dangerous Goods Requiring a Specification Tank"; (h) in the case of a tank designed for mounting on a truck or trailer platform, the words "This Tank Shall Be Secured to the Truck or Trailer Platform by the Means Provided By the Tank Manufacturer"; and (i) in the case of a skid-equipped tank that provides clearances of at least 300 mm to grade, the words "Suitable for Towing over Graded Surfaces Only".  
SOR/2014-152,92 - (1) The consignor must classify these dangerous goods on the basis of samples. (2) The consignor must make available to the Minister, on reasonable notice given by the Minister, a document that explains the sampling method and includes the following information: (a) the scope of the method; (b) the sampling apparatus; (c) the sampling procedures; (d) the frequency and conditions of sampling; and (e) a description of the quality control management system in place. Many methods are available for the sampling of petroleum products. An example can be found in American Society for Testing and Materials Standard ASTM D4057-12, "Standard Practice for Manual Sampling of Petroleum and Petroleum Products". The frequency and conditions of sampling should allow for the variability of the dangerous goods to ensure representativeness. The classification assigned to the dangerous goods should reflect the properties of the dangerous goods during transport.  
SOR/2014-152,150 - An emergency response assistance plan (ERAP) is required for these dangerous goods under subsection 7.1(6) of Part 7 (Emergency Response Assistance Plan).

Explosive Limit and Limited Quantity Index : 5 L

Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

### Transport by sea

UN-No. (IMDG) : 1268

Proper Shipping Name (IMDG) : PETROLEUM DISTILLATES, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,2,4-trimethylbenzene	CAS-No. 95-63-6	30 - 40%
xylene, mixture of isomers	CAS-No. 1330-20-7	< 5%
cumene	CAS-No. 98-82-8	< 5%
ethylbenzene	CAS-No. 100-41-4	< 5%

#### 1,2,4-trimethylbenzene (95-63-6)

Listed on SARA Section 313 (Specific toxic chemical listings)

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>xylene, mixture of isomers (1330-20-7)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	100 lb
<b>cumene (98-82-8)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ	5000 lb
<b>ethylbenzene (100-41-4)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
CERCLA RQ	1000 lb

### 15.2. International regulations

#### CANADA

<b>AROMATIC 100 (64742-95-6)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.

#### EU-Regulations

No additional information available

#### National regulations

<b>cumene (98-82-8)</b>
Listed on IARC (International Agency for Research on Cancer)
<b>ethylbenzene (100-41-4)</b>
Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

This product can expose you to cumene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

<b>cumene (98-82-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
<b>ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	54

<b>1,2,4-trimethylbenzene (95-63-6)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List

<b>xylene, mixture of isomers (1330-20-7)</b>
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

<b>cumene (98-82-8)</b>
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

# AROMATIC 100

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### ethylbenzene (100-41-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Revision date : 06/12/2019  
Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

SDS US Endura

*The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.*