

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : LACQUER THINNER  
 Product code : TS127

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Crown Paint Company  
 1801 W. Sheridan  
 Oklahoma City, 73106 - United States  
 T 1-405-232-8580

#### 1.4. Emergency telephone number

Emergency number : In the event of an emergency involving dangerous goods:  
 in Canada call CANUTEC at 613-996-6666 or \*666 on a cellular phone.  
 in the US call CHEMTREC at 800-424-9300 (Account Name for US is Polyglass Coatings)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

|                                     |  |
|-------------------------------------|--|
| Flam. Liq. 2                        | H225 - Highly flammable liquid and vapor                                 |
| Acute Tox. 4 (Oral)                 | H302 - Harmful if swallowed  |
| Acute Tox. 4 (Dermal)               | H312 - Harmful in contact with skin                                      |
| Acute Tox. 4 (Inhalation:dust,mist) | H332 - Harmful if inhaled  |
| Skin Irrit. 2                       | H315 - Causes skin irritation  |
| Eye Irrit. 2                        | H319 - Causes serious eye irritation                                     |
| STOT SE 1                           | H370 - Causes damage to organs   |
| STOT SE 3                           | H336 - May cause drowsiness or dizziness                                 |
| STOT RE 2                           | H373 - May cause damage to organs through prolonged or repeated exposure |

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
 H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled  
 H315 - Causes skin irritation  
 H319 - Causes serious eye irritation  
 H336 - May cause drowsiness or dizziness  
 H370 - Causes damage to organs  
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P233 - Keep container tightly closed.  
 P240 - Ground/Bond container and receiving equipment  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 - Wash thoroughly after handling  
 P270 - Do not eat, drink or smoke when using this product.  
 P271 - Use only outdoors or in a well-ventilated area.

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312 - IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P307+P311 - If exposed: Call a poison center/doctor  
P312 - Call a poison center/doctor/physician if you feel unwell  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see 4.1. First aid procedures on this label)  
P322 - Specific treatment (see supplemental first aid instruction on this label)  
P330 - Rinse mouth.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2) to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name     | Product identifier | %       | GHS-US classification   |
|----------|--------------------|---------|---|
| toluene  | (CAS-No.) 108-88-3 | 60 - 70 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304  |
| methanol | (CAS-No.) 67-56-1  | 10 - 20 | Flam. Liq. 2, H225<br>Acute Tox. 3 (Oral), H301<br>Acute Tox. 3 (Dermal), H311<br>Acute Tox. 3 (Inhalation:dust,mist),<br>H331<br>STOT SE 1, H370 |
| acetone  | (CAS-No.) 67-64-1  | 10 - 20 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336   |

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off all contaminated clothing immediately. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Irritation.

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Irritation to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Reactivity : Highly flammable liquid and vapor.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| acetone (67-64-1) |                                     |   |
|-------------------|-------------------------------------|---|
| ACGIH             | ACGIH TWA (ppm)                     | 500 ppm (Acetone; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH             | ACGIH STEL (ppm)                    | 750 ppm (Acetone; USA; Short time value; TLV - Adopted Value)                         |
| ACGIH             | Remark (ACGIH)                      | eye irr; CNS impair; BEI  |
| OSHA              | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 2400 mg/m <sup>3</sup>  |

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| acetone (67-64-1)  |                                     |  |
|--------------------|-------------------------------------|--|
| OSHA               | OSHA PEL (TWA) (ppm)                | 1000 ppm   |
| methanol (67-56-1) |                                     |  |
| ACGIH              | ACGIH TWA (ppm)                     | 200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH              | ACGIH STEL (ppm)                    | 250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)                         |
| ACGIH              | Remark (ACGIH)                      | Headache; eye dam; dizziness; nausea   |
| OSHA               | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 260 mg/m <sup>3</sup>  |
| OSHA               | OSHA PEL (TWA) (ppm)                | 200 ppm  |
| toluene (108-88-3) |                                     |  |
| ACGIH              | ACGIH TWA (ppm)                     | 20 ppm (Toluene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)   |
| ACGIH              | Remark (ACGIH)                      | Visual impair; female repro;   |
| OSHA               | Remark (OSHA)                       | (2) See Table Z-2.   |

### 8.2. Exposure controls

|                                  |  |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Hand protection                  | : Protective gloves.                           |
| Eye protection                   | : Safety glasses.                              |
| Skin and body protection         | : Wear suitable protective clothing.           |
| Respiratory protection           | : Wear respiratory protection.                 |
| Environmental exposure controls  | : Avoid release to the environment.            |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                               |
|---|-------------------------------|
| Physical state                              | : Liquid                      |
|   | : No data available           |
|   | : No data available           |
| Odor threshold                              | : No data available           |
| pH  | : No data available           |
| Melting point                               | : Not applicable              |
| Freezing point                              | : No data available           |
| Boiling point                               | : 56 - 110 °C<br>134 - 230 °F |
| Flash point                                 | : -20 °C<br>-4 °F             |
| Relative evaporation rate (butyl acetate=1) | : No data available           |
| Flammability (solid, gas)                   | : No data available           |
| Explosion limits                            | : 1.4 - 36.5 vol %            |
| Explosive properties                        | : No data available           |
| Oxidizing properties                        | : No data available           |
| Vapor pressure                              | : No data available           |
| Relative density                            | : No data available           |
| Relative vapor density at 20 °C             | : No data available           |
| Specific gravity / density                  | : 0.842 g/cm <sup>3</sup>     |
| Solubility                                  | : No data available           |
| Log Pow                                     | : No data available           |
| Auto-ignition temperature                   | : No data available           |
| Decomposition temperature                   | : No data available           |
| Viscosity                                   | : No data available           |
| Viscosity, kinematic                        | : No data available           |

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic : No data available

### 9.2. Other information

Percent Solids (Weight) : 0 %  
Percent Solids (Volume) : 0 %  
Percent Volatile (Weight) : 100 %  
Percent Volatile (Volume) : 100 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| LACQUER THINNER            |   |
|----------------------------|---|
| ATE US (oral)              | 559.362 mg/kg body weight   |
| ATE US (dermal)            | 1678.086 mg/kg body weight  |
| ATE US (dust, mist)        | 2.797 mg/l/4h   |
| acetone (67-64-1)          |   |
| LD50 oral rat              | 5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)   |
| LD50 dermal rabbit         | 20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; >7426 mg/kg bodyweight; Rabbit; Weight of evidence) |
| LC50 inhalation rat (mg/l) | 71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)   |
| LC50 inhalation rat (ppm)  | 30000 ppm/4h (Rat; Experimental value)  |
| ATE US (oral)              | 5800 mg/kg body weight  |
| ATE US (dermal)            | 20000 mg/kg body weight   |
| ATE US (gases)             | 30000 ppmV/4h   |
| ATE US (vapors)            | 71 mg/l/4h  |
| ATE US (dust, mist)        | 71 mg/l/4h  |
| methanol (67-56-1)         |   |
| LD50 oral rat              | > 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)                            |
| LD50 dermal rabbit         | 15800 mg/kg (Rabbit; Literature study)  |
| LC50 inhalation rat (mg/l) | 85 mg/l/4h (Rat; Literature study)  |
| LC50 inhalation rat (ppm)  | 64000 ppm/4h (Rat; Literature study)  |
| ATE US (oral)              | 100 mg/kg body weight   |
| ATE US (dermal)            | 300 mg/kg body weight   |
| ATE US (gases)             | 64000 ppmV/4h   |
| ATE US (vapors)            | 85 mg/l/4h  |
| ATE US (dust, mist)        | 0.5 mg/l/4h   |

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>toluene (108-88-3)</b>         |   |
|-----------------------------------|---|
| LD50 oral rat                     | > 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit                | 12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)                       |
| LC50 inhalation rat (mg/l)        | > 20 mg/l/4h (Rat; Literature study)  |
| ATE US (dermal)                   | 12223 mg/kg body weight   |
| Skin corrosion/irritation         | : Causes skin irritation.   |
| Serious eye damage/irritation     | : Causes serious eye irritation.  |
| Respiratory or skin sensitization | : Not classified  |
| Germ cell mutagenicity            | : Not classified  |
| Carcinogenicity                   | : Not classified  |

| <b>toluene (108-88-3)</b>                          |  |
|--|--|
| IARC group   | 3 - Not Classifiable   |
| Reproductive toxicity                              | : Not classified   |
| Specific target organ toxicity – single exposure   | : Causes damage to organs. May cause drowsiness or dizziness.        |
| Specific target organ toxicity – repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard                                  | : Not classified   |
| Symptoms/effects after skin contact                | : Irritation.  |
| Symptoms/effects after eye contact                 | : Irritation to eyes.  |

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

| <b>acetone (67-64-1)</b>  |  |
|---------------------------|--|
| LC50 fish 2               | 5540 mg/l (LC50; EU Method C.1; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)                 |
| EC50 Daphnia 2            | 12600 mg/l (LC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)                          |
| <b>methanol (67-56-1)</b> |  |
| LC50 fish 1               | 15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value) |
| EC50 Daphnia 1            | > 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)                 |
| LC50 fish 2               | 10800 mg/l (LC50; 96 h; Salmo gairdneri)   |

### 12.2. Persistence and degradability

| <b>acetone (67-64-1)</b>        |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. |
| Biochemical oxygen demand (BOD) | 1.43 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 1.92 g O <sub>2</sub> /g substance   |
| ThOD                            | 2.2 g O <sub>2</sub> /g substance  |
| BOD (% of ThOD)                 | 0.872 (20 days; Literature study)  |
| <b>methanol (67-56-1)</b>       |  |
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.  |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 1.42 g O <sub>2</sub> /g substance   |
| ThOD                            | 1.5 g O <sub>2</sub> /g substance  |

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>methanol (67-56-1)</b>       |  |
|---------------------------------|--|
| BOD (% of ThOD)                 | 0.8 (Literature study)   |
| <b>toluene (108-88-3)</b>       |  |
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 2.15 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 2.52 g O <sub>2</sub> /g substance   |
| ThOD                            | 3.13 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)                 | 0.69   |

### 12.3. Bioaccumulative potential

| <b>acetone (67-64-1)</b>      |  |
|-------------------------------|--|
| BCF fish 1                    | 0.69 (BCF)   |
| BCF other aquatic organisms 1 | 3 (BCF; BCFWIN)  |
| Log Pow                       | -0.24 (Test data)  |
| Bioaccumulative potential     | Not bioaccumulative.                                       |
| <b>methanol (67-56-1)</b>     |  |
| BCF fish 1                    | < 10 (BCF; 72 h; Leuciscus idus)                           |
| Log Pow                       | -0.77 (Experimental value; Other)                          |
| Bioaccumulative potential     | Low potential for bioaccumulation (BCF < 500).             |
| <b>toluene (108-88-3)</b>     |  |
| BCF fish 2                    | 90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water) |
| Log Pow                       | 2.73 (Experimental value; Other; 20 °C)                    |
| Bioaccumulative potential     | Low potential for bioaccumulation (BCF < 500).             |

### 12.4. Mobility in soil

| <b>acetone (67-64-1)</b>  |   |
|---------------------------|---|
| Surface tension           | 0.0237 N/m                              |
| <b>methanol (67-56-1)</b> |   |
| Surface tension           | 0.023 N/m (20 °C)                       |
| Log Koc                   | Koc,PCKOCWIN v1.66; 1; Calculated value |
| <b>toluene (108-88-3)</b> |   |
| Surface tension           | 0.03 N/m (20 °C)                        |

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                         |   |
|-------------------------|---|
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Additional information  | : Flammable vapors may accumulate in the container.   |

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

|                                |   |
|--------------------------------|---|
| Transport document description | : UN1263 Paint related material, 3, II                          |
| UN-No.(DOT)                    | : UN1263  |
| Proper Shipping Name (DOT)     | : Paint related material  |
| Class (DOT)                    | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 |

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

### Transportation of Dangerous Goods

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

| acetone (67-64-1)  |         |
|--|---------|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Not listed on SARA Section 313 (Specific toxic chemical listings) |         |
| CERCLA RQ  | 5000 lb |
| methanol (67-56-1)   |         |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on SARA Section 313 (Specific toxic chemical listings)     |         |
| CERCLA RQ  | 5000 lb |



# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

CERCLA RQ 1000 lb

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

#### methanol (67-56-1)

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No  | Yes   | No  | No  |                                   |

#### toluene (108-88-3)

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No  | Yes   | Yes   | Yes   | 7000                              |

#### acetone (67-64-1)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### methanol (67-56-1)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### toluene (108-88-3)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Revision date : 06/12/2019

# LACQUER THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

|      |   |
|------|---|
| H225 | Highly flammable liquid and vapor                                 |
| H301 | Toxic if swallowed  |
| H302 | Harmful if swallowed  |
| H304 | May be fatal if swallowed and enters airways                      |
| H311 | Toxic in contact with skin  |
| H312 | Harmful in contact with skin                                      |
| H315 | Causes skin irritation  |
| H319 | Causes serious eye irritation                                     |
| H331 | Toxic if inhaled  |
| H332 | Harmful if inhaled  |
| H336 | May cause drowsiness or dizziness                                 |
| H370 | Causes damage to organs   |
| H373 | May cause damage to organs through prolonged or repeated exposure |

### SDS US Endura

*The information contained here has been compiled from sources considered by Endura Manufacturing Co. Ltd to be dependable and is accurate to the best of the Company's knowledge. However, neither Endura Manufacturing Co. Ltd or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.*